







CAMPO 22-32C

TRAILED SPRAYER WITH HYDRAULIC LIFTING



TECHNICAL DATA

CAMPO 22-32C						Wheel-track (min)	Wheel-track (max)	
	Lt.			Lt.	mm	mm	mm	
CAMPO 22C	2400	BP 281	REMO	300	70	1450	2100	230/95 R36
CAMPO 32C	3200	BP 281	REMO	300	80	1600	2250	270/95 R48

STANDARD EQUIPMENT

Electric pressure regulator REMO 5 ways
 Single pushbutton panel for water and oil
 Inspectionable external suction filter
 3 way deviator for filling
 Empty level
 Left side control panel to hold ground centralized controls
 Double hydraulic agitator through perforated tube and pressure agitators
 Flow control kit for functional testing
 Flowback: delivery pipe pressure reset system
 DEVIOKIT: circuit rinse system even with full tank
 GreenMix T30 premixer with parallelogram
 Comet pump BP 281

FRAME AND CONNECTION TO THE TRACTOR
 Varnished frame with stepladder and platform
 Fixed drawbar with Ø50 eye

CAMPO 22C:
 Square axle 70 mm with adjustable wheel-track (min 1450 - max 2100) and wheelbase
 wheels 230/95 R36 8 holes

CAMPO 32C:
 Square axle 80 mm with adjustable wheel-track (min 1600 - max 2250) and wheelbase
 Wheels 270/95 R48 8 holes

TANK GROUP:
 Facilitated polyethylene tank emptying
 Hinged lid with bayonet joint
 Circuit rinse system with independent tank (capacity 300 l)
 2 circuit rinse rotating jets
 Handwashing tank

Trijet complete with bayonet connection nozzles
 Antidrift double fan nozzles 110°-03 in polymer (suitable for low volume treatments)
 Ceramic fan nozzles 110°-05 brown
 Ceramic fan nozzles 110°-06 grey
 Shock absorbing hydraulic lifting 1400 mm
 OILDRIVE - 1 pair of quick hitches on the tractor needed

Variable geometry

CARDAN SHAFT INCLUDED IN THE PRICE